

## METEOR MINI LED



Ground mounted IP67 LED luminaire.

<b>Mounting:</b>	In the ground
<b>Body material:</b>	Stainless steel & aluminium
<b>Colour:</b>	Stainless steel ring, body standard black RAL 9005
<b>LED module:</b>	LED GU10 retrofit lamp included
<b>Colour temperature:</b>	2700K, 3000K or 4000K available
<b>Colour Rendering Index (CRI):</b>	>80 in standard, other on request
<b>Driver:</b>	N/A
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	- 20°C ... +40°C
<b>IP Class:</b>	IP67
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct
<b>Reflector type:</b>	N/A
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	Clear tempered glass in standard, mat on request
<b>General data:</b>	3 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

IP67 220-240 V 50-60 Hz



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2325.355/827/36D	355	4,6	2700	Ra > 80	15.000	3	4	0,90
2325.370/830/36D	370	4,6	3000	Ra > 80	15.000	3	4	0,90
2325.390/840/36D	390	4,6	4000	Ra > 80	15.000	3	4	0,90

